


Accessories for thermocouple and RTD

Available accessories:

- Miniature and standard connectors for thermocouple;
- PVC insulated, fiberglass insulated, FEP insulated, PFA insulated for extension wire thermocouple;
- FEP insulated, fiberglass insulated, PFA insulated for RTD wire;
- Ceramic sheaths and special sheaths;
- Mineral insulated cable for thermocouple and RTD;



Miniature and standard connectors:

- Sandwich construction, thermoplastic or ceramic body, polarized pins ensure proper connection;
- Diameter 0.2 ÷ 0.8mm wire for miniature connectors, diameter 0.2 ÷ 2.0mm wire for standard connectors, maximum 200°C for thermoplastic body and maximum 650°C for ceramic body;

Extension cable for thermocouple;

- PVC isolation maximum 105°C temperature, PFA isolation maximum 260°C temperature, fiber glass isolation maximum 480°C temperature, metallic strip of copper for strength and immunity EMC;

RTD wire:

- PVC isolation, fiberglass isolation, PFA isolation with 2, 3, 4 copper conductors for temperature up to 480°C;

Ceramic and special sheaths for thermocouple:

- Is use for protection the temperature range 500 ÷ 1800°C;

Mineral insulated cable for thermocouple and RTD:

- Temperature -40 ÷ 1000°C and diameter Ø1.6 ÷ 8mm;

Our company can execute any model of thermocouple and RTD, after customer data and design.