



### Flanged ball valve

**Features :**

- Stainless steel ball valve, DIN 3202 F4 ÷ DN 125 F5;
- Stainless steel flanged valve, DN 15-50 PN 10-40 ÷ DN 65 PN 10/16;



**Technical specification :**

Body, ball, flanged	Stainless steel
DN, PN	DN: 15 ÷ 200, PN: 10 ÷ 40
Working temperature	Max. 180°C

DN	PN	D	L	C	E	f	T	H	H1	P	ISO 5211	A1	A2	B1	B2
15	10-40	15	115	45	95	2	16	48	79	9	F03-F04	6	6	36	42
20	10-40	20	120	58	105	2	18	53	84	9	F03-F04	6	6	36	42
25	10-40	25	125	68	115	2	18	58,5	95	11	F04-F05	6	7	42	50
32	10-40	32	130	78	140	2	18	71	103	11	F04-F05	6	7	42	50
40	10-40	38	140	88	150	3	18	76	111	14	F05-F07	7	9	50	70
50	10-40	50	150	102	165	3	20	85	120	14	F05-F07	7	9	50	70
65	10/16	63,5	170	122	185	3	18	101,5	158,5	17	F07-F10	9	11	70	102
	22						107								
80	10/16	76	180	138	200	3	20	111,5	163	17	F07-F10	9	11	70	102
	24						117								
100	10/16	100	190	158	220	3	20	140	182	22	F10	-	11	-	102
	162			235	24										
125	10/16	125	325	188	250	3	22	183	260	27	F12	14	-	125	-
	270			26											
150	10/16	150	350	212	285	3	22	204	280	27	F12	14	-	125	-
	218			300	28										
200	10	200	400	268	340	3	22	252,5	348	27	F14	14	-	125	-
	16			278	360		26								
	25			285	375		30								
	40														

